Attachment 120:1

SCHEDULE OF AREA, YARD AND BUILDING REQUIREMENTS

Chapter 120: Land Use and Development Ordinance of the Borough of Spotswood

	Minimum Lot Requirements			Minimum Required Yard Depth (feet)							Maximum Height of Principal Building				
				Principal Building			Accessory Building								
Zone	Area (sf)	Lot Width (feet)	Lot Depth (feet)	Front Yard (feet)	Min One Side Yard (feet)	Total Both Side Yards (feet)	Rear Yard (feet)	Side Yard (feet)	Rear Yard (feet)	Max % of Lot Cover by Bldgs	Story	Feet 1	Max % of Impervious Coverage by all Buildings and Pavement	Minimum Gross Floor Area (sf)	
С	2 AC	200	200	50	25	-	50	10	10	35%	2 1/2	35	55%	-	
PE	2 AC	200	200	50	25	-	50	10	10	35%	2 1/2	35	55%	-	
R-10 or	10,000	100	100	25	10	20	25	5	5	20%	2 1/2	35	35%	1,000	
R-10	2 AC	200	200	50	25	50	50	10	25	20%	2 1/2	35	35%	N/A	
R-7.5	7,500	75	100	25	10	20	25	5	5	25%	2 1/2	30	40%	1,000	
R-5	5,000	50	100	25	8	20	25	5	5	30%	2 1/2	30	45%	1,000	
AR-MHP	50 AC		See text of zone for further details								1 ½	20	-	See Zone	
TH	2 AC	250	250	50,30	40	-	40	25	25	30%	2 ½	30	60%	See Zone	
APT	3 AC	250	250	50,30	50	-	50	25	25	30%	2 ½	30	60%	See Zone	
SC	2 AC	250	250	50,10	25	-	25	25	25	30%	2 1/2	30	60%	See Zone	
MSR ²	5,000	50	100	15 ²	5,15	-	60	5	5	50%	2 1/2	$30-35^1$	80%	-	
NC	10,000	100	100	25	10	20	25	10	25	25%	2 ½	35	60%	2,000	
GC	40,000	200	200	30	25	50	30	10	25	20%	2 ½	35	55%	5,000	
LI	60,000	200	300	100	25	50	50	25	25	20%	2 ½	35	50%	10,000	
Rev. 5-1-14															